

Philips Signage Solutions Multi-Touch Display

86"

Powered by Android 500cd/m²

86BDL4152T

Chasing innovation

powered by Android

Amaze your guests with a smarter, faster, signage display. With integrated WiFi, designed for running Android apps, and multiple touch points, it's the next evolution in signage solutions.

Innovative solutions for any signage application

- Save and play content with internal memory
- Android: Run your own app or choose your favorite app to run
- Integrated WiFi
- Enhance your connectivity with an integrated mPCle slot.
- Android: Run your own app or choose your favorite app to run

Maximizing the impact of your message

- CMND: Take control of your displays
- Connect and control your content via the cloud
- Manage settings of multiple displays with CMND & Control
- Create and update content with CMND & Create

Care about you, your business and your audience

- SmartPower for energy saving
- Keep your content up and running with FailOver
- Ensure your content is running with automatic screenshots



Highlights

Powered by Android

With Android OS integrated into the display, you can work with the most developed OS on the planet and save your own app directly into the display. Or, choose from the large library of Android apps and play content from there. With the built-in scheduler, you can daypart your apps and content based on your customer and time of day and with the auto orientation feature, showing content in portrait or landscape is as simple as turning the display.

PCI Slot

With an integrated PCI slot, you can connect a WiFI/bluetooth or 4G LTE module, allowing for even greater communication with the display. Machine to machine communication is also enhanced, with numerous configurations available for customers to use, such as the ability to expand product features or signal-handling capability.

Internal Memory



Save and play content with internal memory. Upload your media into the display and playback content immediately. Working in conjunction with the internal browser, it also serves as a memory cache when streaming online content. If the network ever fails, the internal memory keeps content running by playing a cached version of the content, ensuring that your media stays up even if the network goes down.

WiFi

Integrated WiFi

Proof of Play

Content is king, and with the automatic screenshot feauture, you can make sure that your content is up and running at all times. Screenshots are taken throughout the day, which are then stored in the FTP server. From there, the screenshots can be viewed no matter when, or where you are.

FailOver



Keeping your content up and running is critical for demanding commercial applications. While it is unlikely you will face a content disaster, FailOver provides content protection with a revolutionary technology that plays back-up content on screen in the event of a media player failure. FailOver automatically kicks in when the primary input fails. Simply select a primary input connection and a FailOver connection and your ready for instant protection.

FailOver for Meeting Rooms

Using FailOver, simplify your presentations and videoconferencing. When a meeting or conference room is not in use, background content can run from whatever input source you choose. When the meeting starts and you need to share a presentation or your screen, simply connect your computer and the display automatically switches inputs and shows what's on your screen, with no need to manually switch inputs.

SmartPower



The backlight intensity can be controlled and pre-set by the system to reduce the power consumption by up to 50%, which saves substantially on energy costs.

CMND



A robust display management platform, CMND puts the power back into your hands.


Update and manage content with CMND & Create or control your settings with CMND & Control. It's all possible with CMND.

CMND & Control



With CMND & Control, easily manage multiple displays in a central location. With real time display monitoring, setting and software updates from a remote location, and the ability to customize and configure multiple displays at once, such as video wall or menu board displays, controlling your suite of displays has never been easier.

CMND & Create



Design and create compelling content with CMND & Create, a powerful authoring tool. With a drag and drop interface, preloaded templates, and integrated widgets, you'll be able to amaze your customers with compelling content. Available in portrait and landscape mode.

SmartBrowser



Connect and control your content via the cloud with the integrated HTML5 browser. Using the Chromium based browser, design your content online and connect a single display, or your complete network. Show content in both landscape and portrait mode, with fullHD resolution. Streaming content can also be shown in a PIP (picture-in-picture) window. Simply connect the display to the internet using WiFi or with an RJ45 cable, and enjoy your own created playlists





















Specifications

Connectivity

- Audio output: 3.5mm jack, SPDIF
- Video input: DisplayPort, DVI-D (x1), VGA (Analog D-Sub)
- Audio input: 3.5 mm jack
- Other connections: mPCle, micro SD, micro USB, USB power outlet (5 V. 2 amp), OPS
- · Video output: DisplayPort
- External control: RJ45, RS232C (in/out) 2.5 mm jack, IR (in/out) 3.5 mm jack

Picture/Display

- Diagonal screen size (metric): 217.42 cm
- Diagonal screen size (inch): 85.6 inch
- Aspect ratio: 16:9
- Panel resolution: 3840 x 2160
- Pixel pitch: 0.4935 (H) x 0.4935 (V)
- Optimum resolution: 3840x 2160 @ 60Hz
- Brightness: 500 cd/m²
- Display colors: 1.07 billion
- Contrast ratio (typical): 1200
- Dynamic contrast ratio: 500,000:1
- · Response time (typical): 12 ms
- Viewing angle (horizontal): 178 degree
- Viewing angle (vertical): 178 degree
- Picture enhancement: 3/2 2/2 motion pull down, 3D Combfilter, Motion compens. deinterlacing, 3D MA deinterlacing, Dynamic contrast enhancement, Progressive scan

Convenience

- Placement: Landscape, Portrait
- · Picture in picture: PIP
- Tiled Matrix: Up to 15 x 15
- Screen saving functions: Pixel Shift, Low Bright
- · Keyboard control: Hidden, Lockable
- · Signal loop through: RS232, IR Loopthrough
- · Ease of installation: Smart Insert
- Energy saving functions: Smart Power
- Network controllable: RJ45, RS232, One Wire (HDMI-CEC), HDMI (One Wire)

• Built-in speakers: 2 x 10W RMS

- Mains power: 100 ~ 240 VAC, 50 ~ 60 Hz
- · Consumption (Typical): 262 W
- Consumption (Max): 450 W
- Standby power consumption: <0.5 W

Supported Display Resolution

 Computer formats: 1024 x 768, 60, 75Hz 1024×768, 60,70Hz, 1152 x 864, 60, 70, 75Hz, 1152×900 , 66Hz, 1280×720 , 60,70Hz, 1280×720 768, 60Hz, 75Hz, 1280 × 800, 60,75Hz, 1280 × 960, 60Hz, 1280×1024, 60,67,75Hz, 1360 × 768, 60Hz, 1366 x 768, 60Hz, 1400 x 1050 ,60, 75Hz, 1440 x 1050, 60Hz, 1440 × 900, 60, 75Hz, 1600 × 1200, 60Hz, 1600 × 900, 60Hz, 1680 × 1050, 60Hz, 1920 x 1080, 60Hz, 1920 x 1200, 60Hz, 640 x 350, 70Hz, 640 x 480, 60, 67, 72, 75Hz, 720 x 400, 70Hz, 800 x 600, 56, 60, 72, 75Hz, 832 x 624, 75Hz, 848 x 480, 60Hz, 960 x 720, 60,75Hz, 960x720, 75Hz

- Video formats: 480p, 60Hz, 480i, 60Hz, 1080i, 50Hz, 1080i, 60Hz, 1080p, 50, 60Hz, 4K x 2K, 576i, 50Hz, 576p, 50Hz, 720p, 60Hz
- UHD Formats: 3840 x 2160, 24, 25, 30, 60 Hz, 4096 x 2160, 24 Hz

Dimensions

- Smart Insert mount: 100 x 100 mm, 100 x 200 mm
- Set Width: 1957 mm
- Product weight: 96.21 kg
- Set Height: 1128 mm
- Set Depth: 104.9 mm
- Set Width (inch): 77.05 inch
- · Set Height (inch): 44.4 inch
- Wall Mount: 600(H)x400(V) mm, M8
- Set Depth (inch): 4.13 inch
- Bezel width: 28.4 mm(Even bezel)
- Product weight (lb): 212.1 lb

Operating conditions

- Altitude: 0 ~ 3000 m
- Temperature range (operation): 0 \sim 40 $^{\circ}$ C
- MTBF: 50,000 hour(s)
- Relative humidity: 20 ~ 80 %
- Temperature range (storage): -20 \sim 60 $^{\circ}$ C

Multimedia Applications

- · USB Playback Video: MKV, MP4, MPEG, MPG, TS, VOB, WMV, ASF, AVI, FLV, WEBM
- USB Playback Picture: BMP, JPEG, JPG, PDF
- USB Playback Audio: AAC, M4A, MP3, WMA

Internal Player

- CPU: Dual-Core Cortex-A72 @2GHz, Quad-Core Cortex-A53 @ 1.5GHz
- GPU: ARM Mali-T860 MP4
- Memory: 4GB RAM
- Storage: 64G eMMc

Multi-touch Interactivity

• Touch points: 10 simultaneous touch points

Accessories

- Included accessories: Quick start guide, RS232 cable, AC Power Cord, IR sensor cable (1.8M), Remote Control & AAA Batteries
- Included Accessories: IR sensor cable (1.8 m) (x1), M2 screw (x3), M3 screw (x1), Philips logo (x1), RS232 Daisy chain cable (x1), SD card cover (x1), Wifi dipole antenna (x2)
- Optional accessories: ColourCalibrationKit (CCK4602)
- Stand: BMÓ5922 (Optional)

Miscellaneous

- · On-Screen Display Languages: English, French, German, Spanish, Polish, Turkish, Russian, Italian, Simplified Chinese, Traditional Chinese, Arabic, Japanese, Danish, Dutch, Finnish, Norwegian, Portuguese, Swedish
- Warranty: 3 year warranty
- Regulatory approvals: EnergyStar 7.0, CE, FCC, Class B, UL/cUL, CCC, C-Tick, RoHS, GOST, BSMI, CB, J-Moss, PSE, VCCI



Issue date 2024-03-23

Version: 5.1.1

© 2024 Koninklijke Philips N.V. All Rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

EAN: 87 12581 75355 9

www.philips.com