



Philips
LED Display

140 cm (55")
direct LED Zero Bezel

BDL5587XL

Hold your audience spellbound

with this high performance LCD display

Delivering your marketing messages has never been so stylish. With a super-narrow bezel and a whole host of features, this display can fit in seamlessly as a standalone unit or as part of a striking video wall.

Operational flexibility

- Direct LED Backlight
- DVI Out
- Many Functions. One Wire
- Smart insert in the back cover to place a small PC
- Display Port for faster graphics support
- Network Controllability: RJ45
- Enhanced zoom feature supports tiled matrix applications
- VGA Loop through

Lower total cost of ownership

- SmartPower for energy saving
- Brightness automatically adjusts with ambient conditions

Optimised for public viewing

- Full HD LCD display, 1920 x 1080p
- High brightness for clearer images

PHILIPS
sense and simplicity

Highlights

Direct LED Backlight

Enjoy superior light uniformity with a direct LED backlight, which gives you even greater contrast ratios. Purer whites bring an even wider colour gamut, enhancing the colour rendering and making your viewing experience more enjoyable than ever before. And with substantially lower power consumption, your overall TCO is lower too.

DVI Out

Create a digital video wall of up to 9 displays in a 3 x 3 configuration with a DVI daisy chain. Simply connect the DVI Out port to a DVI in port of another display to create the most stunning video wall experience around.

One Wire

Take full control of your display by running all operational commands, as well as your video signal, through just one single HDMI cable. This unique feature makes it so much easier and more convenient to ensure the smooth running and maintenance of your display. Consumer Electronics Control (CEC) commands make finding out vital information about your display absolute child's play.

RJ45

Simple management of your display is available thanks to the introduction of a LAN (RJ45) port. You can configure each display or find

out the status of each device quickly and conveniently via an RJ45 connection.

Display Port

Enjoy crystal-clear images with the high-bandwidth graphics support of the Display Port. As well as transmitting full high-definition video, the Display Port will also transmit audio, thus, eliminating the need for extra cables.

Smart insert

Professional PC's are part of most public signage installations. Quite often they increase the overall depth to the display and cause a lot of cable clutter. So we have designed this display with Smart insert in the back cover, which is ideal for the integration of a professional small form factor PC. On top of that, the cable management system offers a great solution to keep your cables neat and professional looking.

SmartPower

The backlight intensity can be controlled and pre-set by the system to reduce the power consumption by up to 50%, which saves substantially on energy costs.

Full HD LCD display 1920 x 1080p

This display has a resolution that is referred to as Full HD. The state-of-the-art LCD screen technology has the full high definition

widescreen resolution of 1080 progressive lines, each with 1920 pixels. This allows the best possible picture quality for HD input signals with up to 1080 lines. It produces brilliant flicker-free progressive scan pictures with optimum brightness and superb colours. This vibrant and sharp image will provide you with an enhanced viewing experience.

High brightness


Enjoy a clearer image in areas with greater ambient brightness thanks to the 700 nit panel. Your audience can enjoy better image quality in locations that are away from direct sunlight, yet still brighter than average, optimizing the viewing experience.

Zoom function for tiled matrix

The internal zoom function enables easy implementation of a video wall matrix, without the need for expensive external equipment. Capable of many different configurations, creating a stunning video wall has become simplicity itself.

VGA Loop through

Connect multiple displays to create a video wall of up to 150 displays via a VGA daisy chain thus enhancing your visual experience. With no additional hardware required, they are as simple to install as they are captivating to your audience.



Specifications

Picture/Display

- Diagonal screen size: 55 inch / 139.7 cm
- Panel resolution: 1920 x 1080p
- Optimum resolution: 1920 x 1080 @ 60 Hz
- Brightness: 800 cd/m²
- Contrast ratio (typical): 1400:1
- Aspect ratio: 16:9
- Viewing Angle (H / V): 178 / 178 degree
- Pixel pitch: 0.63 x 0.63 mm
- Display colours: 1.06 Billion
- Picture enhancement: 3/2 - 2/2 motion pull down, 3D Combfilter, Motion compens. deinterlacing, Progressive scan, 3D MA deinterlacing, Dynamic contrast enhancement
- Response time (typical): 10 ms

Technical specifications

- Backlight: Direct LED

Supported Display Resolution

• Computer formats

| Resolution | Refresh rate |
|-------------|-------------------|
| 640 x 480 | 60, 67, 72, 75 Hz |
| 800 x 600 | 56, 60, 72, 75 Hz |
| 1024 x 768 | 60 Hz |
| 1280 x 768 | 60 Hz |
| 1280 x 800 | 60 Hz |
| 1280 x 1024 | 60 Hz |
| 1360 x 768 | 60 Hz |
| 1366 x 768 | 60 Hz |
| 1440 x 900 | 60 Hz |
| 1600 x 1200 | 60 Hz |
| 1920 x 1080 | 60 Hz |
| 1920 x 1200 | 60 Hz |

• Video formats

| Resolution | Refresh rate |
|------------|--------------|
| 480i | 60 Hz |
| 480p | 60 Hz |
| 576p | 50 Hz |
| 576i | 50 Hz |
| 720p | 50, 60 Hz |
| 1080i | 50, 60 Hz |
| 1080p | 50, 60 Hz |

Connectivity

- PC: VGA-in D-Sub 15HD, VGA-out D-Sub 15HD, DVI-D x 1, RS232 D-Sub9, RS232 D-sub9 output, 3.5 mm PC audio input x 1, RJ45

- AV input: Component (BNC) x 1
- Other connections: Display Port, DVI Out, USB, HDMI

Convenience

- Tiled Matrix: Up to 15 x 10
- Signal Loop Through:: DVI, RS232, VGA
- Keyboard control:: Hidden
- Ease of installation: AC Out, Carrying Handles, Smart Insert
- Energy-saving functions:: Ambient light sensor, Smart Power
- Network controllable: RS232, RJ45
- Placement: Portrait, Landscape
- Packaging:: Reusable box
- Remote control signal:: Lockable
- Safety control functions:: Heat Control, Temperature Sensor
- Picture in picture:: PBP, PIP, POP

Dimensions

- Bezel thickness: 5.7 mm A to A
- Set dimensions (W x H x D): 1215 x 686 x 126 mm
- Set dimensions in inch (W x H x D): 47.8 x 27.0 x 5.0 inch
- VESA Mount: 400 x 200 mm

Operating conditions

- Temperature range (operation): 0 - 40 °C
- Relative humidity: 5 - 90 %
- MTBF: 60,000 hour(s)

Power

- Consumption (On mode): 150 W
- Standby power consumption: <1 W

Sound


- Built-in speakers: 2 x 10 W (RMS)

Accessories

- Included accessories: Remote Control, Batteries for remote control, AC Power Cord, VGA cable, User manual on CD-ROM, Quick start guide

Miscellaneous

- On-Screen Display Languages: English, French, German, Italian, Polish, Turkish, Russian, Simplified Chinese



Issue date 2013-03-03

Version: 1.5.1

12 NC: 8670 000 95162
EAN: 87 12581 66000 0

© 2013 Koninklijke Philips Electronics N.V.
All Rights reserved.

Specifications are subject to change without notice.
Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

www.philips.com