

Philips  
Quad shield cable

50 ft

RG6 Compression F connectors

SDW5213W



## Enjoy the best connection

for satellite and digital TV

Enjoy premium picture quality with virtually no signal loss. Connects satellite, antenna and digital cable sources to components.

### Enjoy the best reception quality

- 3X faster than standard RG6 coax
- 24 carat gold-plated connectors optimize signal
- 18 AWG copper-coated steel center conductor

### Enjoy extended durability

- Heavy-duty pliable jacket
- Corrosion-resistant connectors

### Protects against signal loss

- Dielectric insulation
- Aluminum braided shield
- Aluminum foil shield

### Easy installation

- Non-slip ergonomic grip for easy use

**PHILIPS**  
sense and simplicity

Quad shield cable  
50 ft RG6 Compression F connectors

# Specifications

## Inner Carton

- GTIN: 1 06 09585 14964 6
- Number of consumer packagings: 2
- Gross weight: 3.593 lb
- Inner carton (L x W x H): 17.3 x 8.5 x 2.2 inch
- Nett weight: 3.369 lb
- Tare weight: 0.225 lb

## Outer Carton

- GTIN: 2 06 09585 14964 3
- Number of consumer packagings: 12
- Gross weight: 23.126 lb
- Outer carton (L x W x H): 18.1 x 18.1 x 7.7 inch

- Nett weight: 20.212 lb
- Tare weight: 2.914 lb

## Packaging dimensions

- UPC: 6 09585 14964 9
- Number of products included: 1
- Packaging type: Blister
- Packaging dimensions (W x H x D): 8.3 x 11.0 x 1.8 inch
- Gross weight: 1.764 lb
- Nett weight: 1.684 lb
- Tare weight: 0.079 lb

SDW5213W/27

# Highlights

## 3X faster than RG6 coax

Transferring the signal at a far greater speed than standard coaxial cable minimizes signal loss, so you enjoy optimum picture quality and data transfer.

## 24 carat gold-plated connector

24 carat gold-plated connectors ensure the best signal quality for your components.

## 18 AWG copper-coated conductor

The highly conductive composition of this signal conduit maximizes signal transfer for optimum picture quality and data transfer.

## Heavy-duty pliable jacket

Pliable PVC sheathing surrounds the cable, protecting it from wear and tear and ensuring long-term durability.

## Dielectric insulation

Superior insulation material separates the center conductor from the braided shield. By isolating the conductors, it maintains signal integrity, ensuring the best picture quality and optimum data transfer.

## Aluminum braided shield

In concert with the aluminum foil shield, this shield works as a barrier to keep the signal inside the conductors and keep interference out.

## Aluminum foil shield

In concert with the aluminum braided shield, this shield works as a barrier to keep the signal inside the conductors and keep interference out.

## Corrosion-resistant connectors

Compressed brass with 24K gold-electroplated connectors creates a secure and extremely durable connection that optimizes signal quality and delivers the best picture and data transfer.



Issue date 2011-09-09

Version: 1.0.6

12 NC: 8670 000 37363  
UPC: 6 09585 14964 9

© 2011 Koninklijke Philips Electronics N.V.  
All Rights reserved.

Specifications are subject to change without notice.  
Trademarks are the property of Koninklijke Philips  
Electronics N.V. or their respective owners.

[www.philips.com](http://www.philips.com)