

Philips  
Quad shield cable

250 ft

RG6 Spool

SDW5225W



## Enjoy the best connection

for satellite and digital TV

Enjoy premium picture quality with virtually no signal loss. Connects satellite, antenna and digital cable sources to components.

### Enjoy the best reception quality

- 3X faster than standard RG6 coax
- 24 carat gold-plated connectors optimize signal
- 18 AWG copper-coated steel center conductor

### Enjoy extended durability

- Heavy-duty pliable jacket
- Corrosion-resistant connectors

### Protects against signal loss

- Dielectric insulation
- Aluminum braided shield
- Aluminum foil shield

### Easy installation

- Non-slip ergonomic grip for easy use

# PHILIPS

sense and simplicity

# Specifications

## Packaging dimensions

- Packaging dimensions (W x H x D): 20 x 16.5 x 20 cm
- Packaging dimensions (W x H x D): 7.9 x 6.5 x 7.9 inch
- Gross weight: 4.34 kg
- Gross weight: 9.568 lb
- Nett weight: 8.435 lb
- Nett weight: 3.826 kg
- Number of products included: 1
- Packaging type: Carton
- Tare weight: 1.133 lb
- Tare weight: 0.514 kg
- UPC: 6 09585 16337 9

## Outer Carton

- Gross weight: 10.582 lb
- Gross weight: 4.8 kg
- Outer carton (L x W x H): 8.7 x 8.7 x 6.9 inch
- Outer carton (L x W x H): 22 x 22 x 17.5 cm
- Nett weight: 8.435 lb
- Nett weight: 3.826 kg
- Number of consumer packagings: 1
- Tare weight: 2.147 lb
- Tare weight: 0.974 kg
- UPC: 6 09585 16337 9

# Highlights

## Easy grip

This non-slip grip makes connecting your components easy and ergonomically comfortable.

## 3X faster than RG6 coax

Transferring the signal at a far greater speed than standard coaxial cable minimizes signal loss, so you enjoy optimum picture quality and data transfer.

## 24 carat gold-plated connector

24 carat gold-plated connectors ensure the best signal quality for your components.

## 18 AWG copper-coated conductor

The highly conductive composition of this signal conduit maximizes signal transfer for optimum picture quality and data transfer.

## Heavy-duty pliable jacket

Pliable PVC sheathing surrounds the cable, protecting it from wear and tear and ensuring long-term durability.

## Dielectric insulation

Superior insulation material separates the center conductor from the braided shield. By isolating the conductors, it maintains signal integrity, ensuring the best picture quality and optimum data transfer.

## Aluminum braided shield

In concert with the aluminum foil shield, this shield works as a barrier to keep the signal inside the conductors and keep interference out.

## Aluminum foil shield

In concert with the aluminum braided shield, this shield works as a barrier to keep the signal inside the conductors and keep interference out.

## Corrosion-resistant connectors

Compressed brass with 24K gold-electroplated connectors creates a secure and extremely durable connection that optimizes signal quality and delivers the best picture and data transfer.



Issue date 2010-07-14

Version: 2.0.3

12 NC: 8670 000 47973  
UPC: 6 09585 16337 9

© 2010 Koninklijke Philips Electronics N.V.  
All Rights reserved.

Specifications are subject to change without notice.  
Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

[www.philips.com](http://www.philips.com)