

Philips  
Composite video cable

1,5 m

SWV2510



## Ensure a reliable connection

with this composite video cable

Depend on this cable to provide you with a reliable video connection between components.

### Enjoy good picture quality

- Nickel-plated connectors for reliable contact

### Protects against signal loss

- Bare copper shielding

### Easy installation

- Color coded connectors for instant recognition
- Non-slip ergonomic grip for easy use

### Enjoy extended durability

- Flexible PVC jacket
- Rubber strain relief

# PHILIPS

Composite video cable  
1,5 m

# Specifications

## Inner Carton

- Net weight: 1.15 kg

## Outer Carton

- EAN/UPC/GTIN: 87 10895 96082 3
- Quantity: 12
- Gross weight: 1.55 kg
- Tare weight: .4 kg
- Net weight: 1.15 kg
- Length: 225 mm

- Width: 185 mm
- Height: 220 mm

## Dimensions

- Gross weight: .1 kg
- Tare weight: .02 kg
- Net weight: .08 kg
- Product length: 23 cm
- Product dimensions (W x H): 140 x 35 mm

SWV2510/10

# Highlights

## Nickel-plated connectors

Nickel-plated connectors establish a clean contact between the cable and connector for a reliable connection.

## Bare copper shielding

Bare copper shielding protects against signal loss.

## Color-coded connectors

Color coded connections make it easy to install your cable into the correct inputs and outputs

## Easy grip

This non-slip grip makes connecting your components easy and ergonomically comfortable.

## Flexible PVC Jacket

Flexible PVC jacket provided protection to the delicate core of the cable. It also offers extended durability and ease of installation.

## Rubber strain relief

Rubber strain relief provides a secure, yet flexible juncture between the cable and the plug.



Issue date 2014-02-05

Version: 2.0.6

12 NC: 9082 100 06193  
EAN: 87 10895 93343 8

© 2014 Koninklijke Philips N.V.  
All Rights reserved.

Specifications are subject to change without notice.  
Trademarks are the property of Koninklijke Philips N.V.  
or their respective owners.

[www.philips.com](http://www.philips.com)