



Philips  
PAL coax cable

1,5 m  
> 75 dB  
Ferrite core

SWV2824W



## Ensure a reliable connection

with this PAL type coax cable

Depend on this cable to provide you with a reliable audio/video connection between components.

### Enjoy good picture quality

- Gold-plated connectors for better conductivity

### Enjoy good audio quality

- High purity copper conductor for reliable signal transfer

### Protects against signal loss

- Bare copper shielding

### Easy installation

- Non-slip ergonomic grip for easy use

### Enjoy extended durability

- Molded plug for secure connections
- Flexible PVC jacket
- Rubber strain relief

# PHILIPS

PAL coax cable  
1,5 m > 75 dB, Ferrite core

# Specifications

## Packaging dimensions

- Packaging dimensions (W x H x D):  
9.4 x 23.6 x 2.5 cm
- Nett weight: 0.101 kg
- Gross weight: 0.120 kg
- Tare weight: 0.019 kg
- EAN: 87 12581 38037 3
- Number of products included: 1
- Packaging type: Blister

## Outer Carton

- Outer carton (L x W x H): 33.0 x 25.4 x 12.2 cm
- Nett weight: 1.212 kg

- Gross weight: 1.790 kg
- Tare weight: 0.578 kg
- EAN: 87 12581 38039 7
- Number of consumer packagings: 12

## Inner Carton

- Inner carton (L x W x H): 24.4 x 10.4 x 10.2 cm
- Nett weight: 0.404 kg
- Gross weight: 0.540 kg
- Tare weight: 0.136 kg
- EAN: 87 12581 38038 0
- Number of consumer packagings: 4

SWV2824W/10

# Highlights

## Bare copper shielding

Bare copper shielding protects against signal loss.

## Easy grip

This non-slip grip makes connecting your components easy and ergonomically comfortable.

## Flexible PVC Jacket

Flexible PVC jacket provided protection to the delicate core of the cable. It also offers extended durability and ease of installation.

## Gold-plated connectors

Gold-plated connectors provide better conductivity by lowering contact resistance. They also prevent connector deterioration through oxidation.

## High purity copper

This copper conductor provides high accuracy in signal transfer with minimal resistance.

## Molded plug

Molded plugs ensure secure connections between components and offer extended durability.

## Rubber strain relief

Rubber strain relief provides a secure, yet flexible juncture between the cable and the plug.



Issue date 2014-02-11

Version: 1.0.9

12 NC: 8670 000 35465  
EAN: 87 12581 38037 3

© 2014 Koninklijke Philips N.V.  
All Rights reserved.

Specifications are subject to change without notice.  
Trademarks are the property of Koninklijke Philips N.V.  
or their respective owners.

[www.philips.com](http://www.philips.com)