

Philips
Component A/V cable

6 ft

Stereo Audio

SWV3312W



Turn up your viewing experience

Step up to a better audio/video connection between components.

Enjoy better picture quality

- 24 carat gold-plated connectors optimize signal

Enjoy better audio quality

- High purity copper conductor for reliable signal transfer

Protects against signal loss

- Copper braided reinforced aluminum shielding

Easy installation

- Color coded connectors for instant recognition
- Plug and play for easy use

Enjoy extended durability

- Flexible PVC jacket
- Protective metal shell for extended durability
- Rubber strain relief

PHILIPS

sense and simplicity

Specifications

Outer Carton

- Gross weight: 0.907 kg
- GTIN: 1 06 09585 15138 0
- Outer carton (L x W x H): 27.9 x 20.3 x 12.7 cm
- Nett weight: 0.544 kg
- Number of consumer packagings: 4
- Tare weight: 0.363 kg

Packaging dimensions

- Packaging dimensions (W x H x D):
19.7 x 26.7 x 4.8 cm
- Gross weight: 0.227 kg
- Nett weight: 0.136 kg
- Number of products included: 1
- Packaging type: Blister
- Tare weight: 0.091 kg
- UPC: 6 09585 15138 3

Highlights

24 carat gold-plated connector

24 carat gold-plated connectors ensure the best signal quality for your components.

High purity copper

This copper conductor provides high accuracy in signal transfer with minimal resistance.

Braided shielding

Copper braided reinforced aluminum shielding protects against signal loss and interference.

Plug and play

Plug and play offers easy installation of components without time-consuming installations.

Color-coded connectors

Color coded connections make it easy to install your cable into the correct inputs and outputs

Metal shell

The metal shell protects the internal connection of the cable. It ensures durability and the reliability of your connection.

Flexible PVC Jacket

Flexible PVC jacket provided protection to the delicate core of the cable. It also offers extended durability and ease of installation.

Rubber strain relief

Rubber strain relief provides a secure, yet flexible juncture between the cable and the plug.

