

Philips
Scart cable

3.0 m

SWV6325



Enjoy the ultimate viewing experience

with this premium a/v cable

Take your components to optimum performance. This top of the line cable offers the best connection for transferring audio/video signals between components.

Enjoy superior picture quality

- 24 carat gold-plated connectors optimize signal
- Split center pin for better signal transfer

Enjoy better audio quality

- High purity copper conductor for reliable signal transfer
- Dense conductor for better signal transfer
- Stranded conductor extends durability

Protects against signal loss

- 100% aluminum shielding
- Oxygen-free copper conductor for ideal signal transfer
- Copper braided shielding
- Foam Polyethylene (FPE) Dielectric

Easy installation

- Non-slip ergonomic grip for easy use
- Plug and play for easy use

PHILIPS

Scart cable
3.0 m

Specifications

Packaging Data

- Quantity: 1
- EAN/UPC/GTIN: 87 10895 93473 2
- Gross weight: .9 kg
- Tare weight: .13 kg
- Net weight: .77 kg
- Length: 265 mm
- Width: 195 mm
- Height: 100 mm

Inner Carton

- EAN/UPC/GTIN: 87 10895 97042 6
- Quantity: 2
- Gross weight: 1.94 kg
- Tare weight: .6 kg

- Net weight: 1.34 kg
- Length: 280 mm
- Width: 175 mm
- Height: 210 mm

Outer Carton

- EAN/UPC/GTIN: 87 10895 97043 3
- Quantity: 4
- Gross weight: 4.55 kg
- Tare weight: 1.87 kg
- Net weight: 2.68 kg
- Length: 370 mm
- Width: 300 mm
- Height: 230 mm

SWV6325/10

Highlights

24 carat gold-plated connector

24 carat gold-plated connectors ensure the best signal quality for your components.

Split center pin

The split center pin allows for better signal transfer and an improved connection to the component inputs.

100% aluminum shielding

This protective layer of aluminum guards against electromagnetic interference for improved signal quality.

Twisted high purity OFC

This oxygen-free copper conductor provides the highest accuracy in signal transfer with minimal resistance.

Copper braided shielding

This protective layer of copper blocks radio frequency interference for improved signal quality.

FPE Dielectric

Foam Polyethylene (FPE) dielectric is a superior insulation material that protects against signal loss.

Easy grip

This non-slip grip makes connecting your components easy and ergonomically comfortable.

Plug and play

Plug and play offers easy installation of components without time-consuming installations.



Issue date 2019-04-24

Version: 2.0.7

12 NC: 9082 100 06394
EAN: 87 10895 93473 2

© 2019 Koninklijke Philips N.V.
All Rights reserved.

Specifications are subject to change without notice.
Trademarks are the property of Koninklijke Philips N.V.
or their respective owners.

www.philips.com